

Underscore[®] Rectangle

66" x 36" Heated BubbleMassage™ air bath, VibrAcoustic®

K-1173-GHVB

Features

- 122 airjets release thousands of heated bubbles that surround, support, and massage the body.
- Variable-speed blower lets you adjust massage intensity to 18 levels.
- Built-in heater.
- Automatic and manual purge cycles remove residual water from air channels after use.
- 60-minute automatic shutoff timer.
- Six concealed speakers send sound waves through the water to gently massage the body.
- Four original instrumental compositions offer different levels of relaxation.
- Fully-adjustable volume above and below the water.
- Customize your experience with the high-resolution color touch screen.
- Six transducers and a control amplifier with 25' (7620 mm) of wiring.
- Slotted overflow allows for deep soaking.
- Generous 66" length provides spacious bathing for up to two people.
- Integral lumbar support.
- Keypad control.
- Textured bottom surface.
- Syncs with devices enabled with BLUETOOTH[®] wireless technology including smartphones, MP3 players, tablets, and laptops located up to 33 feet away.*

Material

Acrylic.

Technology

- Heated BubbleMassage[™] technology warms and humidifies air before it enters the bath.
- VibrAcoustic calms and soothes with sound vibration technology.
- VibrAcoustic system functions as a stereo system when bath is not in use.

Installation

- Drop-in or undermount.
- Reversible drain.
- 120V electrical requirement allows for easy installation with standard outlet.
- Requires three dedicated circuits.

Required Products/Accessories

- K-7271 Brass Slotted Overflow Bath Drain or
 - K-7272 PVC Slotted Overflow Bath Drain



Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 CSA C22.2 No. 218.2

KOHLER[®] Hydrotherapy Components Five-Year Limited Warranty KOHLER[®] Plastic Baths and Receptors Lifetime Limited Warranty

See website for detailed warranty information.

The BLUETOOTH® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Kohler Co. is under license. Other trademarks and trade names are those of their respective owners.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	NY	Dune
	95	lce™ Grey
	58	Thunder™ Gr
	7	Black Black™




ey



Underscore® Rectangle

66" x 36" Heated BubbleMassage™ air bath, VibrAcoustic®

K-1173-GHVB



Required Electrical Service

Three dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Blower:	120 V, 15 A, 60 Hz
Air bath:	120 V, 15 A, 60 Hz
Amplifier:	120 V, 15 A, 60 Hz

Technical Information

All product dimensions are nominal. Drop-in, Undermount Installation: End Drain location: Basin area, bottom: 44-1/2" x 26-1/2" (1130 mm x 673 mm) Basin area, top: 60-1/4" x 30-1/4" (1530 mm x 768 mm) Weight: 115 lbs (52.2 kg) Minimum floor load: 64 lbs/ft² (312.5 kg/m²) Water depth: 17-3/4" (451 mm) Water capacity: 102 gal (386.1 L) Cutout: Drop-in, 65" x 35" (1651 mm x 889 mm) Electrical component Blower: 120 V, 10 A, 60 Hz Air bath: 120 V, 5 A, 60 Hz rating: Amplifier: 120 V, 1.1 A, 60 Hz

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

